



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 46.86x5.97 - FKM - FPM - Viton - 80 Shore A - Braun - ORS38668

<https://www.o-ring-stocks.eu/de/o-ring-46.86x5.97-fkm-fpm-viton-80-shore-a-braun-ors38668>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 38668                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Ringe - 80 Shore A - Braun |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Bruin                            |
| Farbe         | Brown                            |

### Kernspezifikationen

|             |      |
|-------------|------|
| Genehmigung | None |
|-------------|------|

|                   |                                                       |
|-------------------|-------------------------------------------------------|
| Alternativer Name | Viton® - FKM                                          |
| Chemischer Name   | Fluorocarbon Rubber                                   |
| Description 2     | O-ring FKM - FPM - Viton 46.86x5.97                   |
| Größe im Text     | forty six comma eighty six by five comma ninety seven |
| Markennamen       | Viton® - Du Pont - 3M - Solvay - Daikin               |
| Material          | FKM - FPM - Viton                                     |
| Packungseinheit   | O-ring                                                |
| Produkte name     | O-ring 46.86x5.97 FPM - Viton                         |

### Alternative Größe

|                        |              |
|------------------------|--------------|
| DIN 3771 Größentabelle | 46.86x5.97   |
| SMS 1586 Größentabelle | 46.86 X 5.97 |

### Kernspezifikationen

|                        |            |
|------------------------|------------|
| CS (Schnur Starke)     | 5.97 mm    |
| Härte                  | 80 Shore A |
| ID (Inner Durchmesser) | 46.86 mm   |
| Temperatur Max         | 205 °C     |
| Temperatur Min         | -20 °C     |