



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 354.97x5.33 - FFKM - FFPM - Dampf - Heißwasser - 75 Shore A -

<https://www.o-ring-stocks.eu/de/o-ring-354.97x5.33-ffkm-ffpm-dampf-heisswasser-75-shore-a-schwarz-kalrez-1050lf-ors108700-gleichwertig>

Specificaties

Productnummer	108700
Merk	Eurolast
Categorie	FFKM O-Ringe - 75 Shore A - F758ZSR
Materiaal	FFKM - FFPM
Kleur	Zwart
Farbe	Black

Kernspezifikationen

Genehmigung	Steam. Hot Water
-------------	------------------

Alternativer Name	FFPM – Dupont Kalrez
-------------------	----------------------

Chemischer Name	Perfluoroelastomer
-----------------	--------------------

Description 2	O-ring FFKM - FFPM 354.97x5.33
---------------	--------------------------------

Equal to	Kalrez® 1050LF . Chemraz® 555 . Chemraz® 605 . Perflour® V8545-75 . Simriz® 487 . Isolast® J9512 . Polymax P300B8ST . Evolast N8SR
----------	--

Größe im Text	three hundred and fifty four comma ninety seven by five comma thirty three
---------------	---

Markennamen	Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax
-------------	---

Material	FFKM - FFPM
----------	-------------

Packungseinheit	O-ring
-----------------	--------

Produkte name	O-ring 354.97x5.33 FFKM
---------------	-------------------------

Alternative Größe

AS568 Größentabelle	AS 137
---------------------	--------

DIN 3771 Größentabelle	354.97x5.33
------------------------	-------------

SMS 1586 Größentabelle	354.97 X 5.33
------------------------	---------------

Kernspezifikationen

CS (Schnur Starke)	5.33 mm
--------------------	---------

Härte	75 Shore A
-------	------------

ID (Inner Durchmesser)	354.97 mm
------------------------	-----------

Temperatur Max	330 °C
----------------	--------

Specificaties

Temperatur Min	-15 °C
----------------	--------