



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 34.65x1.78 - HNBR - 70 Shore A - Schwarz - ORS49621

<https://www.o-ring-stocks.eu/de/o-ring-34.65x1.78-hnbr-70-shore-a-schwarz-ors49621>

### Specificaties

|               |                                     |
|---------------|-------------------------------------|
| Productnummer | 49621                               |
| Merk          | Eurolast                            |
| Categorie     | HNBR O-Ringe - 70 Shore A - Schwarz |
| Materiaal     | HNBR - Buna                         |
| Kleur         | Zwart                               |
| Farbe         | Black                               |

### Kernspezifikationen

|             |      |
|-------------|------|
| Genehmigung | None |
|-------------|------|

|                   |                                                         |
|-------------------|---------------------------------------------------------|
| Alternativer Name | Hydrogenated Nitrile Butadiene Rubber                   |
| Chemischer Name   | Hydrogenated nitrile rubber                             |
| Description 2     | O-ring HNBR - 34.65x1.78                                |
| Größe im Text     | thirty four comma sixty five by one comma seventy eight |
| Markennamen       | LG Chem - Lanxess and Zeon                              |
| Material          | HNBR                                                    |
| Packungseinheit   | O-ring                                                  |
| Produkte name     | O-ring 34.65x1.78 HNBR                                  |

### Alternative Größe

|                        |              |
|------------------------|--------------|
| AS568 Größentabelle    | AS 028       |
| DIN 3771 Größentabelle | 34.65x1.78   |
| SMS 1586 Größentabelle | 34.65 X 1.78 |

### Kernspezifikationen

|                        |            |
|------------------------|------------|
| CS (Schnur Starke)     | 1.78 mm    |
| Härte                  | 70 Shore A |
| ID (Inner Durchmesser) | 34.65 mm   |
| Temperatur Max         | 150 °C     |
| Temperatur Min         | -25 °C     |