



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 107.32x5.33 - PTFE - Teflon - Weiss - FDA - ORS42789

<https://www.o-ring-stocks.eu/de/o-ring-107.32x5.33-ptfe-teflon-weiss-fda-ors42789>

### Specificaties

|               |                    |
|---------------|--------------------|
| Productnummer | 42789              |
| Merk          | Eurolast           |
| Categorie     | PTFE O-Ringe - FDA |
| Materiaal     | PTFE – Teflon      |
| Kleur         | Wit                |
| Farbe         | White              |

### Kernspezifikationen

|             |     |
|-------------|-----|
| Genehmigung | FDA |
|-------------|-----|

|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| Alternativer Name | TEFLON®                                                           |
| Chemischer Name   | Polytetrafluoretheen                                              |
| Description 2     | O-ring PTFE - Teflon 107.32x5.33                                  |
| Größe im Text     | one hundred and seven comma thirty two by five comma thirty three |
| Markennamen       | Lanxess - Zeon - and LG Chem                                      |
| Material          | PTFE – Teflon                                                     |
| Packungseinheit   | O-ring                                                            |
| Produkte name     | O-ring 107.32x5.33 PTFE - Teflon                                  |

### Alternative Größe

|                        |               |
|------------------------|---------------|
| AS568 Größentabelle    | AS 347        |
| DIN 3771 Größentabelle | 107.32x5.33   |
| SMS 1586 Größentabelle | 107.32 X 5.33 |

### Kernspezifikationen

|                        |           |
|------------------------|-----------|
| CS (Schnur Starke)     | 5.33 mm   |
| ID (Inner Durchmesser) | 107.32 mm |
| Temperatur Max         | 200 °C    |
| Temperatur Min         | -260 °C   |