



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 468.76x6.99 - FFKM - FFPM - Hohe Temp - 75 Shore A - Schwarz -

<https://www.o-ring-stocks.eu/de/o-ring-468.76x6.99-ffkm-ffpm-hohe-temp-75-shore-a-schwarz-ors84247>

### Specificaties

|               |                                     |
|---------------|-------------------------------------|
| Productnummer | 84247                               |
| Merk          | Eurolast                            |
| Categorie     | FFKM O-Ringe - 75 Shore A - F757Z75 |
| Materiaal     | FFKM - FFPM                         |
| Kleur         | Zwart                               |
| Farbe         | Black                               |

### Kernspezifikationen

|             |                  |
|-------------|------------------|
| Genehmigung | High Temperature |
|-------------|------------------|

|                   |                                                                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Alternativer Name | FFPM – Dupont Kalrez                                                                                                                            |
| Chemischer Name   | Perfluoroelastomer                                                                                                                              |
| Description 2     | O-ring FFKM - FFPM 468.76x6.99                                                                                                                  |
| Equal to          | Dupont Kalrez 6375 - Fruedenberg Simriz 495 - Greene Tweed Chemraz 605 - Parker Parafluor V8910-75 - PPE Perlast G80A - Trelleborg Isolast 9440 |
| Größe im Text     | four hundred and sixty eight comma seventy six by six comma ninety nine                                                                         |
| Markennamen       | Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®                                |
| Material          | FFKM - FFPM                                                                                                                                     |
| Packungseinheit   | O-ring                                                                                                                                          |
| Produkte name     | O-ring 195x7 FFKM                                                                                                                               |

### Alternative Größe

|                        |               |
|------------------------|---------------|
| AS568 Größentabelle    | AS 466        |
| DIN 3771 Größentabelle | 468.76x6.99   |
| SMS 1586 Größentabelle | 468.76 X 6.99 |

### Gleichwertig an

|                                                   |                           |
|---------------------------------------------------|---------------------------|
| Dupont Kalrez® Äquivalent                         | Dupont Kalrez 6375        |
| Freudenberg Simriz® Äquivalent                    | Fruedenberg Simriz 495    |
| Greene Tweed Chemraz® Äquivalent                  | Greene Tweed Chemraz 605  |
| Parker Parafluor® Äquivalent                      | Parker Parafluor V8910-75 |
| Precision Polymer Engineering Perlast® Äquivalent | PPE Perlast G80A          |

**Specificaties**

|                                |                         |
|--------------------------------|-------------------------|
| Trelleborg Isolast® Äquivalent | Trellebrog Isolast 9440 |
| <b>Kernspezifikationen</b>     |                         |
| CS (Schnur Starke)             | 6.99 mm                 |
| Härte                          | 75 Shore A              |
| ID (Inner Durchmesser)         | 468.76 mm               |
| Temperatur Max                 | 340 °C                  |
| Temperatur Min                 | -15 °C                  |