



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 240.67x6.99 - FFKM - FFPM - Hohe Temp - 75 Shore A - Schwarz -

<https://www.o-ring-stocks.eu/de/o-ring-240.67x6.99-ffkm-ffpm-hohe-temp-75-shore-a-schwarz-ors84031>

Specificaties

Productnummer	84031
Merk	Eurolast
Categorie	FFKM O-Ringe - 75 Shore A - F757Z75
Materiaal	FFKM - FFPM
Kleur	Zwart
Farbe	Black

Kernspezifikationen

Genehmigung	High Temperature
-------------	------------------

Alternativer Name	FFPM – Dupont Kalrez
-------------------	----------------------

Chemischer Name	Perfluoroelastomer
-----------------	--------------------

Description 2	O-ring FFKM - FFPM 240.67x6.99
---------------	--------------------------------

Equal to	Dupont Kalrez 6375 - Fruedenberg Simriz 495 - Greene Tweed Chemraz 605 - Parker Parafluor V8910-75 - PPE Perlast G80A - Trelleborg Isolast 9440
----------	---

Größe im Text	two hundred and forty comma sixty seven by six comma ninety nine
---------------	--

Markennamen	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®
-------------	--

Material	FFKM - FFPM
----------	-------------

Packungseinheit	O-ring
-----------------	--------

Produkte name	O-ring 174.2x5.7 FFKM
---------------	-----------------------

Alternative Größe

AS568 Größentabelle	AS 272
---------------------	--------

DIN 3771 Größentabelle	240.67x6.99
------------------------	-------------

SMS 1586 Größentabelle	240.67 X 6.99
------------------------	---------------

Gleichwertig an

Dupont Kalrez® Äquivalent	Dupont Kalrez 6375
---------------------------	--------------------

Freudenberg Simriz® Äquivalent	Fruedenberg Simriz 495
--------------------------------	------------------------

Greene Tweed Chemraz® Äquivalent	Greene Tweed Chemraz 605
----------------------------------	--------------------------

Parker Parafluor® Äquivalent	Parker Parafluor V8910-75
------------------------------	---------------------------

Precision Polymer Engineering Perlast® Äquivalent	PPE Perlast G80A
---	------------------

Specificaties

Trelleborg Isolast® Äquivalent	Trellebrog Isolast 9440
Kernspezifikationen	
CS (Schnur Starke)	6.99 mm
Härte	75 Shore A
ID (Inner Durchmesser)	240.67 mm
Temperatur Max	340 °C
Temperatur Min	-15 °C