



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 120.4x1.78 - FFKM - FFPM - Hohe Temp - 75 Shore A - Schwarz -

<https://www.o-ring-stocks.eu/de/o-ring-120.4x1.78-ffkm-ffpm-hohe-temp-75-shore-a-schwarz-ors83712>

Specificaties

Productnummer	83712
Merk	Eurolast
Categorie	FFKM O-Ringe - 75 Shore A - F757Z75
Materiaal	FFKM - FFPM
Kleur	Zwart
Farbe	Black

Kernspezifikationen

Genehmigung	High Temperature
-------------	------------------

Alternativer Name	FFPM – Dupont Kalrez
Chemischer Name	Perfluoroelastomer
Description 2	O-ring FFKM - FFPM 120.4x1.78
Equal to	Dupont Kalrez 6375 - Fruedenberg Simriz 495 - Greene Tweed Chemraz 605 - Parker Parafluor V8910-75 - PPE Perlast G80A - Trelleborg Isolast 9440

Größe im Text	one hundred and twenty comma forty by one comma seventy eight
---------------	---

Markennamen	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®
-------------	--

Material	FFKM - FFPM
----------	-------------

Packungseinheit	O-ring
-----------------	--------

Produkte name	O-ring 133.4x3.53 FFKM
---------------	------------------------

Alternative Größe

AS568 Größentabelle	AS 048
DIN 3771 Größentabelle	120.4x1.78
SMS 1586 Größentabelle	120.4 X 1.78

Gleichwertig an

Dupont Kalrez® Äquivalent	Dupont Kalrez 6375
Freudenberg Simriz® Äquivalent	Fruedenberg Simriz 495
Greene Tweed Chemraz® Äquivalent	Greene Tweed Chemraz 605
Parker Parafluor® Äquivalent	Parker Parafluor V8910-75
Precision Polymer Engineering Perlast® Äquivalent	PPE Perlast G80A

Specificaties

Trelleborg Isolast® Äquivalent

Trellebrog Isolast 9440

Kernspezifikationen

CS (Schnur Starke)1.78 mm

Härte75 Shore A

ID (Inner Durchmesser)120.4 mm

Temperatur Max340 °C

Temperatur Min-15 °C