



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 114x1.78 - FFKM - FFPM - Hohe Temp - 75 Shore A - Schwarz -

<https://www.o-ring-stocks.eu/de/o-ring-114x1.78-ffkm-ffpm-hohe-temp-75-shore-a-schwarz-ors83669>

Specificaties

Productnummer	83669
Merk	Eurolast
Categorie	FFKM O-Ringe - 75 Shore A - F757Z75
Materiaal	FFKM - FFPM
Kleur	Zwart
Farbe	Black

Kernspezifikationen

Genehmigung	High Temperature
-------------	------------------

Alternativer Name	FFPM – Dupont Kalrez
-------------------	----------------------

Chemischer Name	Perfluoroelastomer
-----------------	--------------------

Description 2	O-ring FFKM - FFPM 114x1.78
---------------	-----------------------------

Equal to	Dupont Kalrez 6375 - Fruedenberg Simriz 495 - Greene Tweed Chemraz 605 - Parker Parafluor V8910-75 - PPE Perlast G80A - Trelleborg Isolast 9440
----------	---

Größe im Text	one hundred and fourteen zero by one comma seventy eight
---------------	--

Markennamen	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®
-------------	--

Material	FFKM - FFPM
----------	-------------

Packungseinheit	O-ring
-----------------	--------

Produkte name	O-ring 129.77x3.53 FFKM
---------------	-------------------------

Alternative Größe

AS568 Größentabelle	AS 047
---------------------	--------

DIN 3771 Größentabelle	114x1.78
------------------------	----------

SMS 1586 Größentabelle	114 X 1.78
------------------------	------------

Gleichwertig an

Dupont Kalrez® Äquivalent	Dupont Kalrez 6375
---------------------------	--------------------

Freudenberg Simriz® Äquivalent	Fruedenberg Simriz 495
--------------------------------	------------------------

Greene Tweed Chemraz® Äquivalent	Greene Tweed Chemraz 605
----------------------------------	--------------------------

Parker Parafluor® Äquivalent	Parker Parafluor V8910-75
------------------------------	---------------------------

Precision Polymer Engineering Perlast® Äquivalent	PPE Perlast G80A
---	------------------

Specificaties

Trelleborg Isolast® Äquivalent

Trellebrog Isolast 9440

Kernspezifikationen

CS (Schnur Starke)1.78 mm

Härte75 Shore A

ID (Inner Durchmesser)114 mm

Temperatur Max340 °C

Temperatur Min-15 °C