



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 7.66x1.78 - FFKM - FFPM - Hohe Temp - 75 Shore A - Schwarz -

<https://www.o-ring-stocks.eu/de/o-ring-7.66x1.78-ffkm-ffpm-hohe-temp-75-shore-a-schwarz-ors82971>

Specificaties

Productnummer	82971
Merk	Eurolast
Categorie	FFKM O-Ringe - 75 Shore A - F757Z75
Materiaal	FFKM - FFPM
Kleur	Zwart
Farbe	Black

Kernspezifikationen

Genehmigung	High Temperature
-------------	------------------

Alternativer Name	FFPM – Dupont Kalrez
Chemischer Name	Perfluoroelastomer
Description 2	O-ring FFKM - FFPM 7.66x1.78
Equal to	Dupont Kalrez 6375 - Fruedenberg Simriz 495 - Greene Tweed Chemraz 605 - Parker Parafluor V8910-75 - PPE Perlast G80A - Trelleborg Isolast 9440
Größe im Text	seven comma sixty six by one comma seventy eight
Markennamen	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®
Material	FFKM - FFPM
Packungseinheit	O-ring
Produkte name	O-ring 70x5.7 FFKM

Alternative Größe

AS568 Größentabelle	AS 204
DIN 3771 Größentabelle	7.66x1.78
SMS 1586 Größentabelle	7.66 X 1.78

Gleichwertig an

Dupont Kalrez® Äquivalent	Dupont Kalrez 6375
Freudenberg Simriz® Äquivalent	Fruedenberg Simriz 495
Greene Tweed Chemraz® Äquivalent	Greene Tweed Chemraz 605
Parker Parafluor® Äquivalent	Parker Parafluor V8910-75
Precision Polymer Engineering Perlast® Äquivalent	PPE Perlast G80A
Trelleborg Isolast® Äquivalent	Trelleborg Isolast 9440

Specificaties

Kernspezifikationen

CS (Schnur Starke)	1.78 mm
Härte	75 Shore A
ID (Inner Durchmesser)	7.66 mm
Temperatur Max	340 °C
Temperatur Min	-15 °C