



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 50.17x5.33 - FEP-FKM - FDA - ORS152949

<https://www.o-ring-stocks.eu/de/o-ring-50.17x5.33-fep-fkm-fda-ors152949>

### Specificaties

|               |                               |
|---------------|-------------------------------|
| Productnummer | 152949                        |
| Merk          | Eurolast                      |
| Categorie     | FEP Ummantelt - Viton O-Ringe |
| Materiaal     | FKM - FPM - Viton             |
| Kleur         | Zwart                         |
| Farbe         | Black                         |

### Kernspezifikationen

|             |     |
|-------------|-----|
| Genehmigung | FDA |
|-------------|-----|

|                   |                                                  |
|-------------------|--------------------------------------------------|
| Alternativer Name | Viton® - FKM                                     |
| Chemischer Name   | Fluorocarbon Rubber                              |
| Description 2     | O-ring FKM - FPM - Viton 50.17x5.33              |
| Größe im Text     | fifty comma seventeen by five comma thirty three |
| Markennamen       | Teflex FEP-O-SEAL®                               |
| Material          | FKM - FPM - Viton                                |
| Packungseinheit   | O-ring                                           |
| Produkte name     | O-ring 50.17x5.33 FKM - FPM - Viton              |

### Alternative Größe

|                        |            |
|------------------------|------------|
| DIN 3771 Größentabelle | 50.17x5.33 |
| ISO 3601 Größentabelle | 50.17x5.33 |
| SMS 1586 Größentabelle | 50.17x5.33 |

### Kernspezifikationen

|                             |           |
|-----------------------------|-----------|
| CS (Schnur Starke)          | 5.33 mm   |
| ID (Inner Durchmesser)      | 50.17 mm  |
| Temperatur Max              | 205 °C    |
| Temperatur Min              | -20 °C    |
| Tolerance (CS) DIN 7715-M2F | ± 0,30    |
| Tolerance (ID) DIN 7715-M2F | ± 0,94935 |