



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 80x5 - FEP-FKM - FPM - Viton - FDA - ORS112908

<https://www.o-ring-stocks.eu/de/o-ring-80x5-fep-fkm-fpm-viton-fda-ors112908>

### Specificaties

|               |                               |
|---------------|-------------------------------|
| Productnummer | 6521953                       |
| Merk          | Eurolast                      |
| Categorie     | FEP Ummantelt - Viton O-Ringe |
| Materiaal     | FEP-FKM - FPM - Viton         |
| Kleur         | Zwart                         |
| Farbe         | Black                         |

### Kernspezifikationen

|             |     |
|-------------|-----|
| Genehmigung | FDA |
|-------------|-----|

|                   |                                                    |
|-------------------|----------------------------------------------------|
| Alternativer Name | FEP - Viton® - FKM / FEP encapsulated Viton® - FKM |
| Chemischer Name   | Teflon® fluoropolymer - Viton                      |
| Description 2     | O-ring FEP-FKM - FPM - Viton 80x5                  |
| Größe im Text     | eighty zero by five zero                           |
| Markennamen       | Teflex FEP-O-SEAL®                                 |
| Material          | FEP-FKM - FPM - Viton                              |
| Packungseinheit   | O-ring                                             |
| Produkte name     | O-ring 80x5 FEP-FPM - Viton                        |

### Alternative Größe

|                        |        |
|------------------------|--------|
| AS568 Größentabelle    | AS 453 |
| DIN 3771 Größentabelle | 80x5   |
| SMS 1586 Größentabelle | 80 X 5 |

### Kernspezifikationen

|                             |        |
|-----------------------------|--------|
| CS (Schnur Starke)          | 5 mm   |
| ID (Inner Durchmesser)      | 80 mm  |
| Temperatur Max              | 205 °C |
| Tolerance (CS) DIN 7715-M2F | ± 0,60 |
| Tolerance (ID) DIN 7715-M2F | ± 0,70 |