



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 234.32x5.33 - EDPM - Schwefel - 70 Shore A - Schwarz - ORS14893

<https://www.o-ring-stocks.eu/de/o-ring-234.32x5.33-edpm-schwefel-70-shore-a-schwarz-ors14893>

### Specificaties

|               |                           |
|---------------|---------------------------|
| Productnummer | 14893                     |
| EAN           | 6150547455482             |
| Merk          | Eurolast                  |
| Categorie     | EPDM O-Ringe - 70 Shore A |
| Materiaal     | EPDM                      |
| Kleur         | Zwart                     |
| Farbe         | Black                     |

### Kernspezifikationen

|                 |                                                                         |
|-----------------|-------------------------------------------------------------------------|
| Genehmigung     | None                                                                    |
| Chemischer Name | Ethylene propylene diene monomer                                        |
| Description 2   | O-ring EPDM 234.32x5.33                                                 |
| Größe im Text   | two hundred and thirty four comma thirty two by five comma thirty three |
| Markennamen     | Dow Chemical - ExxonMobil - and Lion Elastomers                         |
| Material        | EPDM                                                                    |
| Packungseinheit | O-ring                                                                  |
| Produkte name   | O-ring 234.32x5.33 EPDM                                                 |

### Alternative Größe

|                        |               |
|------------------------|---------------|
| AS568 Größentabelle    | AS 374        |
| DIN 3771 Größentabelle | 234.32x5.33   |
| SMS 1586 Größentabelle | 234.32 X 5.33 |

### Kernspezifikationen

|                        |            |
|------------------------|------------|
| CS (Schnur Starke)     | 5.33 mm    |
| Härte                  | 70 Shore A |
| ID (Inner Durchmesser) | 234.32 mm  |
| Temperatur Max         | 125 °C     |
| Temperatur Min         | -40 °C     |
| Vulcanisation          | Sulfur     |