



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 142.24x6.99 - CR - Neoprene - 70 Shore A - Schwarz - ORS39616

<https://www.o-ring-stocks.eu/de/o-ring-142.24x6.99-cr-neoprene-70-shore-a-schwarz-ors39616>

### Specificaties

|               |               |
|---------------|---------------|
| Productnummer | 39616         |
| Merk          | Eurolast      |
| Categorie     | CR O-Ringe    |
| Materiaal     | CR - Neoprene |
| Kleur         | Zwart         |
| Farbe         | Black         |

### Kernspezifikationen

|             |      |
|-------------|------|
| Genehmigung | None |
|-------------|------|

|                   |                                                                      |
|-------------------|----------------------------------------------------------------------|
| Alternativer Name | Neoprene                                                             |
| Chemischer Name   | Chloroprene rubber / chlorobutadiene rubber                          |
| Description 2     | O-ring CR - Neoprene 142.24x6.99                                     |
| Größe im Text     | one hundred and forty two comma twenty four by six comma ninety nine |
| Markennamen       | Neoprene                                                             |
| Material          | CR - Neoprene                                                        |
| Packungseinheit   | O-ring                                                               |
| Produkte name     | O-ring 142.24x6.99 CR - Neopreen                                     |

### Alternative Größe

|                        |               |
|------------------------|---------------|
| AS568 Größentabelle    | AS 434        |
| DIN 3771 Größentabelle | 142.24x6.99   |
| SMS 1586 Größentabelle | 142.24 X 6.99 |

### Kernspezifikationen

|                        |            |
|------------------------|------------|
| CS (Schnur Starke)     | 6.99 mm    |
| Härte                  | 70 Shore A |
| ID (Inner Durchmesser) | 142.24 mm  |
| Temperatur Max         | 100 °C     |
| Temperatur Min         | -40 °C     |