



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 557.61x5.33 - CR - Neoprene - 70 Shore A - Schwarz - ORS48396

<https://www.o-ring-stocks.eu/de/o-ring-557.61x5.33-cr-neoprene-70-shore-a-schwarz-ors48396>

### Specificaties

|               |               |
|---------------|---------------|
| Productnummer | 48396         |
| Merk          | Eurolast      |
| Categorie     | CR O-Ringe    |
| Materiaal     | CR - Neoprene |
| Kleur         | Zwart         |
| Farbe         | Black         |

### Kernspezifikationen

|             |      |
|-------------|------|
| Genehmigung | None |
|-------------|------|

|                   |                                                                         |
|-------------------|-------------------------------------------------------------------------|
| Alternativer Name | Neoprene                                                                |
| Chemischer Name   | Chloroprene rubber / chlorobutadiene rubber                             |
| Description 2     | O-ring CR - Neoprene 557.61x5.33                                        |
| Größe im Text     | five hundred and fifty seven comma sixty one by five comma thirty three |
| Markennamen       | Neoprene                                                                |
| Material          | CR - Neoprene                                                           |
| Packungseinheit   | O-ring                                                                  |
| Produkte name     | O-ring 557.61x5.33 CR - Neopreen                                        |

### Alternative Größe

|                        |               |
|------------------------|---------------|
| AS568 Größentabelle    | AS 391        |
| DIN 3771 Größentabelle | 557.61x5.33   |
| SMS 1586 Größentabelle | 557.61 X 5.33 |

### Kernspezifikationen

|                        |            |
|------------------------|------------|
| CS (Schnur Starke)     | 5.33 mm    |
| Härte                  | 70 Shore A |
| ID (Inner Durchmesser) | 557.61 mm  |
| Temperatur Max         | 100 °C     |
| Temperatur Min         | -40 °C     |