



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 36.09x3.53 - FFKM - FFPM - 75 Shore A - Schwarz - Kalrez® 6375 -

<https://www.o-ring-stocks.eu/de/o-ring-36.09x3.53-ffkm-ffpm-75-shore-a-schwarz-kalrez-6375-ors181871-gleichwertig>

Specificaties

Productnummer	181871
Merk	Eurolast
Categorie	FFKM O-Ringe - 75 Shore A - F757Z75
Materiaal	FFKM - FFPM
Kleur	ZWART
Farbe	Black

Kernspezifikationen

Genehmigung	None
-------------	------

Alternativer Name	FFPM – Dupont Kalrez
Chemischer Name	Perfluoroelastomer
Description 2	O-ring FFKM - FFPM 36.09x3.53
Equal to	Dupont Kalrez® 6375 - Fruedenberg Simriz® 495 - Greene Tweed Chemraz® 605 - Parker Parafluor® V8910-75 - PPE Perlast® G80A - Trelleborg Isolast® 9440
Größe im Text	thirty six comma nine by three comma fifty three
Markennamen	Kalrez® - Simriz® - Chemraz® - Spectrum® - Triazinico® - Isolast® - Parofluor® - Fluorez® - Perlast® - Perfluor®
Material	FFKM - FFPM
Packungseinheit	O-ring
Produkte name	O-ring 36.09x3.53 FFKM

Alternative Größe

AS568 Größentabelle	AS 127
DIN 3771 Größentabelle	36.09 x 3.53
SMS 1586 Größentabelle	36.09x3.53

Gleichwertig an

Dupont Kalrez® Äquivalent	Dupont Kalrez® 6375
Freudenberg Simriz® Äquivalent	Fruedenberg Simriz® 495
Greene Tweed Chemraz® Äquivalent	Greene Tweed Chemraz® 605
Parker Parafluor® Äquivalent	Parker Parafluor® V8910-75
Precision Polymer Engineering Perlast® Äquivalent	PPE Perlast® G80A
Trelleborg Isolast® Äquivalent	Trelleborg Isolast® 9440

Specificaties

Kernspezifikationen

CS (Schnur Starke)	3.53 mm
Härte	75 Shore A
ID (Inner Durchmesser)	36.09 mm
Temperatur Max	270 °C
Temperatur Min	-40 °C