



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-Ring 47.22x3.53 - EPDM - 80 Shore A - Schwarz - PEROX - ORS118758

<https://www.o-ring-stocks.eu/de/o-ring-47.22x3.53-epdm-80-shore-a-schwarz-perox-ors118758>

### Specificaties

|               |                                   |
|---------------|-----------------------------------|
| Productnummer | 118758                            |
| Merk          | Eurolast                          |
| Categorie     | EPDM O-Ringe - 80 Shore A - Perox |
| Materiaal     | EPDM                              |
| Kleur         | Zwart                             |
| Farbe         | Black                             |

### Kernspezifikationen

|             |      |
|-------------|------|
| Genehmigung | None |
|-------------|------|

|                 |                                                         |
|-----------------|---------------------------------------------------------|
| Chemischer Name | Ethylene propylene diene monomer                        |
| Description 2   | O-ring EPDM 47.22x3.53                                  |
| Größe im Text   | forty seven comma twenty two by three comma fifty three |
| Markennamen     | Dow Chemical - ExxonMobil - and Lion Elastomers         |
| Material        | EPDM                                                    |
| Packungseinheit | O-ring                                                  |
| Produkte name   | O-Ring 47.22x3.53 EPDM                                  |

### Alternative Größe

|                        |              |
|------------------------|--------------|
| AS568 Größentabelle    | AS 225       |
| DIN 3771 Größentabelle | 47.22x3.53   |
| SMS 1586 Größentabelle | 47.22 X 3.53 |

### Kernspezifikationen

|                        |            |
|------------------------|------------|
| CS (Schnur Starke)     | 3.53 mm    |
| Härte                  | 80 Shore A |
| ID (Inner Durchmesser) | 47.22 mm   |
| Temperatur Max         | 150 °C     |
| Temperatur Min         | -40 °C     |
| Vulcanisation          | Peroxide   |