



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 123.42x3.53 - PTFE - Teflon - Blanc - FDA - ORS42807

<https://www.o-ring-stocks.eu/fr/joint-torique-123.42x3.53-ptfe-teflon-blanc-fda-ors42807>

### Specificaties

|               |                    |
|---------------|--------------------|
| Productnummer | 42807              |
| Merk          | Eurolast           |
| Categorie     | PTFE O-Rings - FDA |
| Materiaal     | PTFE – Teflon      |
| Kleur         | Wit                |
| Kleur         | White              |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                                                         |
|-----------------------|-------------------------------------------------------------------------|
| Alternatieve benaming | TEFLON®                                                                 |
| Chemische Benaming    | Polytetrafluoretheen                                                    |
| Extra omschrijving    | O-ring 123.42x3.53 PTFE - Teflon                                        |
| Maat in tekst         | one hundred and twenty three comma forty two by three comma fifty three |
| Materiaal             | PTFE – Teflon                                                           |
| Merknamen             | Lanxess - Zeon - and LG Chem                                            |
| Omschrijving-2        | O-ring PTFE - Teflon 123.42x3.53                                        |
| Verpakkingseenheid    | O-ring                                                                  |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 249        |
| DIN 3771 Maat | 123.42x3.53   |
| SMS 1586 Maat | 123.42 X 3.53 |

### Basis Specificaties

|                     |           |
|---------------------|-----------|
| CS (snoer dikte)    | 3.53 mm   |
| ID (binnendiameter) | 123.42 mm |
| Temperatuur Max     | 200 °C    |
| Temperatuur Min     | -260 °C   |