



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 278.99x3.53 - CR - Neoprene - 70 Shore A - Noir - ORS175546

<https://www.o-ring-stocks.eu/fr/joint-torique-278.99x3.53-cr-neoprene-70-shore-a-noir-ors175546>

### Specificaties

|               |               |
|---------------|---------------|
| Productnummer | 175546        |
| Merk          | Eurolast      |
| Categorie     | CR O-Rings    |
| Materiaal     | CR - Neoprene |
| Kleur         | ZWART         |
| Kleur         | Black         |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                                            |
|-----------------------|----------------------------------------------------------------------------|
| Alternatieve benaming | Neoprene                                                                   |
| Chemische Benaming    | Chloroprene rubber / chlorobutadiene rubber                                |
| Extra omschrijving    | O-ring 278.99x3.53                                                         |
| Maat in tekst         | two hundred and seventy eight comma ninety nine by three comma fifty three |
| Materiaal             | CR - Neoprene                                                              |
| Merknamen             | Neoprene                                                                   |
| Omschrijving-2        | O-ring CR - Neoprene 278.99x3.53                                           |
| Verpakkingseenheid    | O-ring                                                                     |

### Alternative maat

|               |               |
|---------------|---------------|
| DIN 3771 Maat | 278.99 x 3.53 |
| SMS 1586 Maat | 278.99x3.53   |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 278.99 mm  |
| Temperatuur Max     | 100 °C     |
| Temperatuur Min     | -40 °C     |