



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 50.4x3.53 - VMQ - MVQ - Silicone - 60 Shore A - Rouge -

<https://www.o-ring-stocks.eu/fr/joint-torique-50.4x3.53-vmq-mvq-silicone-60-shore-a-rouge-ors50158>

### Specificaties

|               |                                             |
|---------------|---------------------------------------------|
| Productnummer | 50158                                       |
| Merk          | Eurolast                                    |
| Categorie     | VMQ - MVQ - Silicone - O-Rings - 60 Shore A |
| Materiaal     | VMQ - MVQ - Silicone                        |
| Kleur         | Rood                                        |
| Kleur         | Red                                         |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Alternatieve benaming | Silicone Rubber - PVMQ                        |
| Chemische Benaming    | Vinyl Methyl Silicone                         |
| Extra omschrijving    | O-ring 50.4x3.53 VMQ - Silicone               |
| Maat in tekst         | fifty comma forty by three comma fifty three  |
| Materiaal             | Silicone - VMQ - MVQ                          |
| Merknamen             | Eriks - Wacker - Eastern Seals - and BlueStar |
| Omschrijving-2        | O-ring VMQ - MVQ - Silicone 50.4x3.53         |
| Verpakkingseenheid    | O-ring                                        |

### Alternative maat

|               |             |
|---------------|-------------|
| AS568 Maat    | AS 226      |
| DIN 3771 Maat | 50.4x3.53   |
| SMS 1586 Maat | 50.4 X 3.53 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 60 Shore A |
| ID (binnendiameter) | 50.4 mm    |
| Temperatuur Max     | 210 °C     |
| Temperatuur Min     | -50 °C     |