



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

Joint Torique 660x7 - FFKM - FFPM - Haute Temp - FDA - EC1935/2004 -

<https://www.o-ring-stocks.eu/fr/joint-torique-660x7-ffkm-ffpm-haute-temp-fda-ec19352004-usp-class-vi-80-shore-a-blanc-ors188782>

Specificaties

Productnummer	188782
Merk	Eurolast
Categorie	FFKM O-Rings - 80 Shore A - F808W95 - Wit
Materiaal	FFKM - FFPM
Kleur	WIT
Kleur	White

Basis Specificaties

Keurmerk	FDA 21 CFR 177.2400. EC1935/2004. USP Class VI. 3A-Sanitary Standard
----------	--

Alternatieve benaming	FFPM – Dupont Kalrez
Chemische Benaming	Perfluoroelastomer
Equivalent	Perlast® G80H . (G75 S)
Extra omschrijving	O-ring 660x7 FFKM - FFPM
Maat in tekst	six hundred and sixty zero by seven zero
Materiaal	FFKM - FFPM
Merknamen	Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax
Omschrijving-2	O-ring FFKM - FFPM 660x7
Verpakkingseenheid	O-ring

Alternative maat

DIN 3771 Maat	660 x 7
ISO 3601 Maat	660x7
SMS 1586 Maat	660x7

Basis Specificaties

CS (snoer dikte)	7 mm
Hardheid	80 Shore A
ID (binnendiameter)	660 mm
Temperatuur Max	300 °C
Temperatuur Min	-15 °C