



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## Joint Torique 21.59x5.33 - FKM - FPM - Viton - 75 Shore A - Brun -

<https://www.o-ring-stocks.eu/fr/joint-torique-21.59x5.33-fkm-fpm-viton-75-shore-a-brun-ors131712>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 131712                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 75 Shore A - Bruin |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | BRUIN                            |
| Kleur         | Brown                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                        |
|-----------------------|--------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                           |
| Chemische Benaming    | Fluorocarbon Rubber                                    |
| Extra omschrijving    | O-ring 21.59x5.33 FKM - FPM - Viton                    |
| Maat in tekst         | twenty one comma fifty nine by five comma thirty three |
| Materiaal             | FKM - FPM - Viton                                      |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                |
| Omschrijving-2        | O-ring FKM - FPM - Viton 21.59x5.33                    |
| Verpakkingseenheid    | O-ring                                                 |

### Alternative maat

|               |            |
|---------------|------------|
| AS568 Maat    | AS 316     |
| DIN 3771 Maat | 21.59x5.33 |
| ISO 3601 Maat | 21.59x5.33 |
| SMS 1586 Maat | 21.59x5.33 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.33 mm    |
| Hardheid            | 75 Shore A |
| ID (binnendiameter) | 21.59 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |