



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 329.57x6.99 - FKM - FPM - Viton - 70 Shore A - Vert

<https://www.o-ring-stocks.eu/fr/joint-torique-329.57x6.99-fkm-fpm-viton-70-shore-a-vert-ors41993>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 41993                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 70 Shore A - Groen |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Groen                            |
| Kleur         | Green                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                                          |
|-----------------------|--------------------------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                                             |
| Chemische Benaming    | Fluorocarbon Rubber                                                      |
| Extra omschrijving    | O-ring 329.57x6.99 FPM - Viton                                           |
| Maat in tekst         | three hundred and twenty nine comma fifty seven by six comma ninety nine |
| Materiaal             | FKM - FPM - Viton                                                        |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                                  |
| Omschrijving-2        | O-ring FKM - FPM - Viton 329.57x6.99                                     |
| Verpakkingseenheid    | O-ring                                                                   |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 455        |
| DIN 3771 Maat | 329.57x6.99   |
| SMS 1586 Maat | 329.57 X 6.99 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 6.99 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 329.57 mm  |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |