



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 4x5 - FKM - FPM - Viton - 80 Shore A - Bruin - ORS6225

<https://www.o-ring-stocks.eu/fr/joint-torique-4x5-fkm-fpm-viton-80-shore-a-brun-ors6225>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 6225                             |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Bruin |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Bruin                            |
| Kleur         | Brown                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                         |
|-----------------------|-----------------------------------------|
| Alternatieve benaming | Viton® - FKM                            |
| Chemische Benaming    | Fluorocarbon Rubber                     |
| Extra omschrijving    | O-ring 4x5 FPM - Viton                  |
| Maat in tekst         | four zero by five zero                  |
| Materiaal             | FKM - FPM - Viton                       |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin |
| Omschrijving-2        | O-ring FKM - FPM - Viton 4x5            |
| Verpakkingseenheid    | O-ring                                  |

### Alternative maat

|               |       |
|---------------|-------|
| DIN 3771 Maat | 4x5   |
| SMS 1586 Maat | 4 X 5 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5 mm       |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 4 mm       |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |