



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 12x1.6 - FKM - 80 Shore A - Vert -ORS166852

<https://www.o-ring-stocks.eu/fr/joint-torique-12x1.6-fkm-80-shore-a-vert-ors166852>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 166852                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Zwart |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | GROEN                            |
| Kleur         | Green                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                         |
|-----------------------|-----------------------------------------|
| Alternatieve benaming | Viton® - FKM                            |
| Chemische Benaming    | Fluorocarbon Rubber                     |
| Extra omschrijving    | O-ring 12x1.6 FKM - FPM - Viton         |
| Maat in tekst         | twelve zero by one comma sixty          |
| Materiaal             | FKM - FPM - Viton                       |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin |
| Omschrijving-2        | O-ring FKM - FPM - Viton 12x1.6         |
| Verpakkingseenheid    | O-ring                                  |

### Alternative maat

|               |        |
|---------------|--------|
| DIN 3771 Maat | 12x1.6 |
| ISO 3601 Maat | 12x1.6 |
| SMS 1586 Maat | 12x1.6 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 1.6 mm     |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 12 mm      |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |