



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 215.58x2.62 - NBR - Nitrile - 70 Shore A - Noir - ORS1248

<https://www.o-ring-stocks.eu/fr/joint-torique-215.58x2.62-nbr-nitrile-70-shore-a-noir-ors1248>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 1248                     |
| EAN           | 6150549044080            |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 70 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | Zwart                    |
| Kleur         | Black                    |

### Basis Specificaties

|                       |                                                                  |
|-----------------------|------------------------------------------------------------------|
| Keurmerk              | None                                                             |
| Alternatieve benaming | Nitrile Rubber - NBR                                             |
| Chemische Benaming    | Acrylonitrile butadiene rubber                                   |
| Extra omschrijving    | O-ring 215.58x2.62 Nitrile NBR                                   |
| Maat in tekst         | two hundred and fifteen comma fifty eight by two comma sixty two |
| Materiaal             | NBR - Nitrile                                                    |
| Merknamen             | Lanxess - Zeon - and LG Chem                                     |
| Omschrijving-2        | O-ring NBR - Nitrile 215.58x2.62                                 |
| Verpakkingseenheid    | O-ring                                                           |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 173        |
| DIN 3771 Maat | 215.58x2.62   |
| SMS 1586 Maat | 215.58 X 2.62 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 2.62 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 215.58 mm  |
| Temperatuur Max     | 135 °C     |
| Temperatuur Min     | -30 °C     |