



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 506.86x6.99 - EDPM - Soufre - 70 Shore A - Noir - ORS5710

<https://www.o-ring-stocks.eu/fr/joint-torique-506.86x6.99-edpm-soufre-70-shore-a-noir-ors5710>

### Specificaties

|               |                           |
|---------------|---------------------------|
| Productnummer | 5710                      |
| EAN           | 6150549658690             |
| Merk          | Eurolast                  |
| Categorie     | EPDM O-Rings - 70 Shore A |
| Materiaal     | EPDM                      |
| Kleur         | Zwart                     |
| Kleur         | Black                     |

### Basis Specificaties

|                    |                                                                |
|--------------------|----------------------------------------------------------------|
| Keurmerk           | None                                                           |
| Chemische Benaming | Ethylene propylene diene monomer                               |
| Extra omschrijving | O-ring 506.86x6.99 EPDM                                        |
| Maat in tekst      | five hundred and six comma eighty six by six comma ninety nine |
| Materiaal          | EPDM                                                           |
| Merknamen          | Dow Chemical - ExxonMobil - and Lion Elastomers                |
| Omschrijving-2     | O-ring EPDM 506.86x6.99                                        |
| Verpakkingseenheid | O-ring                                                         |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 469        |
| DIN 3771 Maat | 506.86x6.99   |
| SMS 1586 Maat | 506.86 X 6.99 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 6.99 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 506.86 mm  |
| Temperatuur Max     | 125 °C     |
| Temperatuur Min     | -40 °C     |
| Vulkanisatie        | Sulfur     |