



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 679x5.34 - NBR - Nitrile - 70 Shore A - Noir - ORS149166

<https://www.o-ring-stocks.eu/fr/joint-torique-679x5.34-nbr-nitrile-70-shore-a-noir-ors149166>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 149166                   |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 70 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | ZWART                    |
| Kleur         | Black                    |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Alternatieve benaming | Nitrile Rubber - NBR                                        |
| Chemische Benaming    | Acrylonitrile butadiene rubber                              |
| Extra omschrijving    | O-ring 679x5.34 Nitrile NBR                                 |
| Maat in tekst         | six hundred and seventy nine zero by five comma thirty four |
| Materiaal             | NBR - Nitrile                                               |
| Merknamen             | Lanxess - Zeon - and LG Chem                                |
| Omschrijving-2        | O-ring NBR - Nitrile 679x5.34                               |
| Verpakkingseenheid    | O-ring                                                      |

### Alternative maat

|               |            |
|---------------|------------|
| DIN 3771 Maat | 679x5.34   |
| ISO 3601 Maat | 679x5.34   |
| SMS 1586 Maat | 679 x 5.34 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.34 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 679 mm     |
| Temperatuur Max     | 135 °C     |
| Temperatuur Min     | -30 °C     |