



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 75x2 - FEP-FKM - FDA - ORS173279

<https://www.o-ring-stocks.eu/fr/joint-torique-75x2-fep-fkm-fda-ors173279>

### Specificaties

|               |                     |
|---------------|---------------------|
| Productnummer | 173279              |
| Merk          | Eurolast            |
| Categorie     | FEP - Viton O-Rings |
| Materiaal     | FKM - FPM - Viton   |
| Kleur         | Zwart               |
| Kleur         | Black               |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                         |
|-----------------------|-----------------------------------------|
| Alternatieve benaming | Viton® - FKM                            |
| Chemische Benaming    | Fluorocarbon Rubber                     |
| Extra omschrijving    | O-ring 75x2 FKM - FPM - Viton           |
| Maat in tekst         | seventy five zero by two zero           |
| Materiaal             | FKM - FPM - Viton                       |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin |
| Omschrijving-2        | O-ring FKM - FPM - Viton 75x2           |
| Verpakkingseenheid    | O-ring                                  |

### Alternative maat

|               |      |
|---------------|------|
| DIN 3771 Maat | 75x2 |
| ISO 3601 Maat | 75x2 |
| SMS 1586 Maat | 75x2 |

### Basis Specificaties

|                              |        |
|------------------------------|--------|
| CS (snoer dikte)             | 2 mm   |
| ID (binnendiameter)          | 75 mm  |
| Temperatuur Max              | 205 °C |
| Temperatuur Min              | -20 °C |
| Tolerantie (CS) DIN 7715-M2F | ± 0,10 |
| Tolerantie (ID) DIN 7715-M2F | N/A    |