



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 202.57x5.33 - NBR - Nitrile - 80 Shore A - Noir - ORS3936

<https://www.o-ring-stocks.eu/fr/joint-torique-202.57x5.33-nbr-nitrile-80-shore-a-noir-ors3936>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 3936                     |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 80 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | Zwart                    |
| Kleur         | Black                    |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                                  |
|-----------------------|------------------------------------------------------------------|
| Alternatieve benaming | Nitrile Rubber - NBR                                             |
| Chemische Benaming    | Acrylonitrile butadiene rubber                                   |
| Extra omschrijving    | O-ring 202.57x5.33 Nitrile NBR                                   |
| Maat in tekst         | two hundred and two comma fifty seven by five comma thirty three |
| Materiaal             | NBR - Nitrile                                                    |
| Merknamen             | Lanxess - Zeon - and LG Chem                                     |
| Omschrijving-2        | O-ring NBR - Nitrile 202.57x5.33                                 |
| Verpakkingseenheid    | O-ring                                                           |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 369        |
| DIN 3771 Maat | 202.57x5.33   |
| SMS 1586 Maat | 202.57 X 5.33 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.33 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 202.57 mm  |
| Temperatuur Max     | 135 °C     |
| Temperatuur Min     | -30 °C     |