



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 50.16x5.33 - NBR - Nitrile - 80 Shore A - Noir - ORS3897

<https://www.o-ring-stocks.eu/fr/joint-torique-50.16x5.33-nbr-nitrile-80-shore-a-noir-ors3897>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 3897                     |
| Merk          | Eurolast                 |
| Categorie     | NBR O-Rings - 80 Shore A |
| Materiaal     | Nitrile NBR-Buna         |
| Kleur         | Zwart                    |
| Kleur         | Black                    |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                |
|-----------------------|------------------------------------------------|
| Alternatieve benaming | Nitrile Rubber - NBR                           |
| Chemische Benaming    | Acrylonitrile butadiene rubber                 |
| Extra omschrijving    | O-ring 50.16x5.33 Nitrile NBR                  |
| Maat in tekst         | fifty comma sixteen by five comma thirty three |
| Materiaal             | NBR - Nitrile                                  |
| Merknamen             | Lanxess - Zeon - and LG Chem                   |
| Omschrijving-2        | O-ring NBR - Nitrile 50.16x5.33                |
| Verpakkingseenheid    | O-ring                                         |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 329       |
| DIN 3771 Maat | 50.16x5.33   |
| SMS 1586 Maat | 50.16 X 5.33 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.33 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 50.16 mm   |
| Temperatuur Max     | 135 °C     |
| Temperatuur Min     | -30 °C     |