



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 113.67x5.33 - FEP-VMQ - MVQ - Silicone - FDA - ORS112398

<https://www.o-ring-stocks.eu/fr/joint-torique-113.67x5.33-fep-vmq-mvq-silicone-fda-ors112398>

### Specificaties

|               |                          |
|---------------|--------------------------|
| Productnummer | 6521424                  |
| Merk          | Eurolast                 |
| Categorie     | FEP - Silicone O-Rings   |
| Materiaal     | FEP-VMQ - MVQ - Silicone |
| Kleur         | Rood                     |
| Kleur         | Red                      |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                                                             |
|-----------------------|-----------------------------------------------------------------------------|
| Alternatieve benaming | FEP-VMQ / VMQ - FEP Encapsulated / FEP-Silicone / Silicone FEP Encapsulated |
| Chemische Benaming    | Teflon® fluoropolymer - Silicone                                            |
| Extra omschrijving    | O-ring 113.67x5.33 FEP-VMQ - Silicone                                       |
| Maat in tekst         | one hundred and thirteen comma sixty seven by five comma thirty three       |
| Materiaal             | FEP-VMQ - MVQ - Silicone                                                    |
| Merknamen             | Teflex FEP-O-SEAL®                                                          |
| Omschrijving-2        | O-ring FEP-VMQ - MVQ - Silicone 113.67x5.33                                 |
| Verpakkingseenheid    | O-ring                                                                      |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 103        |
| DIN 3771 Maat | 113.67x5.33   |
| SMS 1586 Maat | 113.67 X 5.33 |

### Basis Specificaties

|                              |             |
|------------------------------|-------------|
| CS (snoer dikte)             | 5.33 mm     |
| ID (binnendiameter)          | 113.67 mm   |
| Temperatuur Max              | 205 °C      |
| Tolerantie (CS) DIN 7715-M2F | ± 0,30 mm   |
| Tolerantie (ID) DIN 7715-M2F | ± 1,0175 mm |