



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 120.02x5.33 - FEP-FKM - FPM - Viton - FDA - ORS35306

<https://www.o-ring-stocks.eu/fr/joint-torique-120.02x5.33-fep-fkm-fpm-viton-fda-ors35306>

### Specificaties

|               |                       |
|---------------|-----------------------|
| Productnummer | 288437                |
| Merk          | Eurolast              |
| Categorie     | FEP - Viton O-Rings   |
| Materiaal     | FEP-FKM - FPM - Viton |
| Kleur         | Zwart                 |
| Kleur         | Black                 |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | FDA |
|----------|-----|

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Alternatieve benaming | FEP - Viton® - FKM / FEP encapsulated Viton® - FKM          |
| Chemische Benaming    | Teflon® fluoropolymer - Viton                               |
| Extra omschrijving    | O-ring 120.02x5.33 FEP-FPM - Viton                          |
| Maat in tekst         | one hundred and twenty comma two by five comma thirty three |
| Materiaal             | FEP-FKM - FPM - Viton                                       |
| Merknamen             | Teflex FEP-O-SEAL®                                          |
| Omschrijving-2        | O-ring FEP-FKM - FPM - Viton 120.02x5.33                    |
| Verpakkingseenheid    | O-ring                                                      |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 351        |
| DIN 3771 Maat | 120.02x5.33   |
| SMS 1586 Maat | 120.02 X 5.33 |

### Basis Specificaties

|                              |           |
|------------------------------|-----------|
| CS (snoer dikte)             | 5.33 mm   |
| ID (binnendiameter)          | 120.02 mm |
| Temperatuur Max              | 205 °C    |
| Tolerantie (CS) DIN 7715-M2F | ± 0,50    |
| Tolerantie (ID) DIN 7715-M2F | ± 1,025   |