



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## Joint Torique 24x1 - VMQ - MVQ - Silicone - FDA - EC1935/2004 - 70 Shore

<https://www.o-ring-stocks.eu/fr/joint-torique-24x1-vmq-mvq-silicone-fda-ec19352004-70-shore-a-rouge-ors17698>

### Specificaties

|               |                                       |
|---------------|---------------------------------------|
| Productnummer | 17698                                 |
| EAN           | 6150547712738                         |
| Merk          | Eurolast                              |
| Categorie     | VMQ O-Rings - 70 Shore A - Rood - FDA |
| Materiaal     | VMQ - MVQ - Silicone                  |
| Kleur         | Rood                                  |
| Kleur         | Red                                   |

### Basis Specificaties

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Keurmerk              | FDA 21 CFR 177.2600 – EC1935/2004             |
| Alternatieve benaming | Silicone Rubber - PVMQ                        |
| Chemische Benaming    | Vinyl Methyl Silicone                         |
| Extra omschrijving    | O-ring 24x1 VMQ - Silicone                    |
| Maat in tekst         | twenty four zero by one zero                  |
| Materiaal             | Silicone - VMQ - MVQ                          |
| Merknamen             | Eriks - Wacker - Eastern Seals - and BlueStar |
| Omschrijving-2        | O-ring VMQ - MVQ - Silicone 24x1              |
| Verpakkingseenheid    | O-ring                                        |

### Alternative maat

|               |        |
|---------------|--------|
| DIN 3771 Maat | 24x1   |
| SMS 1586 Maat | 24 X 1 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 1 mm       |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 24 mm      |
| Temperatuur Max     | 210 °C     |
| Temperatuur Min     | -50 °C     |