



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 20.24x2.62 - VMQ - MVQ - Silicone - FDA - EC1935/2004 - 70 Shore A

<https://www.o-ring-stocks.eu/it/o-ring-20.24x2.62-vmq-mvq-silicone-fda-ec19352004-70-shore-a-rosso-ors138004>

### Specificaties

|               |                                       |
|---------------|---------------------------------------|
| Productnummer | 138004                                |
| Merk          | Eurolast                              |
| Categorie     | VMQ O-Rings - 70 Shore A - Rood - FDA |
| Materiaal     | VMQ - MVQ - Silicone                  |
| Kleur         | ROOD                                  |
| Kleur         | Red                                   |

### Basis Specificaties

|          |                                   |
|----------|-----------------------------------|
| Keurmerk | FDA 21 CFR 177.2600 – EC1935/2004 |
|----------|-----------------------------------|

|                       |                                                 |
|-----------------------|-------------------------------------------------|
| Alternatieve benaming | Silicone Rubber - PVMQ                          |
| Chemische Benaming    | Vinyl Methyl Silicone                           |
| Extra omschrijving    | O-ring 20.24x2.62 VMQ - MVQ - Silicone          |
| Maat in tekst         | twenty comma twenty four by two comma sixty two |
| Materiaal             | Silicone - VMQ - MVQ                            |
| Merknamen             | Eriks - Wacker - Eastern Seals - and BlueStar   |
| Omschrijving-2        | O-ring VMQ - MVQ - Silicone 20.24x2.62          |
| Verpakkingseenheid    | O-ring                                          |

### Alternative maat

|               |            |
|---------------|------------|
| DIN 3771 Maat | 20.24x2.62 |
| ISO 3601 Maat | 20.24x2.62 |
| SMS 1586 Maat | 20.24x2.62 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 2.62 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 20.24 mm   |
| Temperatuur Max     | 210 °C     |
| Temperatuur Min     | -50 °C     |