



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 164.2x5.7 - CR - Neoprene - 70 Shore A - Nero - ORS175444

<https://www.o-ring-stocks.eu/it/o-ring-164.2x5.7-cr-neoprene-70-shore-a-nero-ors175444>

### Specificaties

|               |               |
|---------------|---------------|
| Productnummer | 175444        |
| Merk          | Eurolast      |
| Categorie     | CR O-Rings    |
| Materiaal     | CR - Neoprene |
| Kleur         | ZWART         |
| Kleur         | Black         |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                               |
|-----------------------|---------------------------------------------------------------|
| Alternatieve benaming | Neoprene                                                      |
| Chemische Benaming    | Chloroprene rubber / chlorobutadiene rubber                   |
| Extra omschrijving    | O-ring 164.2x5.7                                              |
| Maat in tekst         | one hundred and sixty four comma twenty by five comma seventy |
| Materiaal             | CR - Neoprene                                                 |
| Merknamen             | Neoprene                                                      |
| Omschrijving-2        | O-ring CR - Neoprene 164.2x5.7                                |
| Verpakkingseenheid    | O-ring                                                        |

### Alternative maat

|               |             |
|---------------|-------------|
| DIN 3771 Maat | 164.2 x 5.7 |
| SMS 1586 Maat | 164.2x5.7   |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.7 mm     |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 164.2 mm   |
| Temperatuur Max     | 100 °C     |
| Temperatuur Min     | -40 °C     |