



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 228.28x2.62 - CR - Neoprene - 70 Shore A - Nero - ORS48265

<https://www.o-ring-stocks.eu/it/o-ring-228.28x2.62-cr-neoprene-70-shore-a-nero-ors48265>

### Specificaties

|               |               |
|---------------|---------------|
| Productnummer | 48265         |
| Merk          | Eurolast      |
| Categorie     | CR O-Rings    |
| Materiaal     | CR - Neoprene |
| Kleur         | Zwart         |
| Kleur         | Black         |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
| Alternatieve benaming | Neoprene                                                               |
| Chemische Benaming    | Chloroprene rubber / chlorobutadiene rubber                            |
| Extra omschrijving    | O-ring 228.28x2.62 CR - Neopreen                                       |
| Maat in tekst         | two hundred and twenty eight comma twenty eight by two comma sixty two |
| Materiaal             | CR - Neoprene                                                          |
| Merkenamen            | Neoprene                                                               |
| Omschrijving-2        | O-ring CR - Neoprene 228.28x2.62                                       |
| Verpakkingseenheid    | O-ring                                                                 |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 175        |
| DIN 3771 Maat | 228.28x2.62   |
| SMS 1586 Maat | 228.28 X 2.62 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 2.62 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 228.28 mm  |
| Temperatuur Max     | 100 °C     |
| Temperatuur Min     | -40 °C     |