



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 701.8x6.99 - FKM - FPM - Viton - 75 Shore A - Marrone - ORS142764

<https://www.o-ring-stocks.eu/it/o-ring-701.8x6.99-fkm-fpm-viton-75-shore-a-marrone-ors142764>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 142764                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 75 Shore A - Bruin |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | BRUIN                            |
| Kleur         | Brown                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                                |
| Chemische Benaming    | Fluorocarbon Rubber                                         |
| Extra omschrijving    | O-ring 701.8x6.99 FKM - FPM - Viton                         |
| Maat in tekst         | seven hundred and one comma eighty by six comma ninety nine |
| Materiaal             | FKM - FPM - Viton                                           |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                     |
| Omschrijving-2        | O-ring FKM - FPM - Viton 701.8x6.99                         |
| Verpakkingseenheid    | O-ring                                                      |

### Alternative maat

|               |            |
|---------------|------------|
| DIN 3771 Maat | 701.8x6.99 |
| ISO 3601 Maat | 701.8x6.99 |
| SMS 1586 Maat | 701.8x6.99 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 6.99 mm    |
| Hardheid            | 75 Shore A |
| ID (binnendiameter) | 701.8 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |