



O-ring-Stocks.eu - Techniparts

Rondweg 26
8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

<https://www.o-ring-stocks.eu/it/o-ring-39.34x2.62-ffkm-ffpm-75-shore-a-nero-kalrez-6375-ors51074-equivalente>

Specificaties

Productnummer	51074
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758Z94
Materiaal	FFKM - FFPM
Kleur	Zwart

Basis Specificaties

Keurmerk	General Purpose (+270°C)
Kleur	Black

Equivalent	Dupont Kalrez 6375, Freudenberg Simriz 495, Greene Tweed Chemraz 605, PPE Perlast G80A, Parker Parafluor V8910-75
------------	---

Materiaal	FFKM - FFPM
-----------	-------------

NIEUW - Details II	N894
--------------------	------

Omschrijving-2	O-ring FFKM - FFPM 39.34x2.62
----------------	-------------------------------

Type Dichting	O-ring
---------------	--------

Alternative maat

AS568 Maat	AS 402
------------	--------

DIN 3771 Maat	39.34x2.62
---------------	------------

Maat in tekst	thirty nine comma thirty four by two comma sixty two
---------------	--

SMS 1586 Maat	39.34 X 2.62
---------------	--------------

Basis Specificaties

CS (Snoer dikte)	2.62 mm
------------------	---------

Hardheid	75 Shore A
----------	------------

ID (Binnendiameter)	39.34 mm
---------------------	----------

Temperatuur Max	270 °C
-----------------	--------

Temperatuur Min	-20 °C
-----------------	--------

Equivalent aan

Dupont Kalrez® Equivalent	Dupont Kalrez 6375
---------------------------	--------------------

Freudenberg Simriz® Equivalent	Freudenberg Simriz 495
--------------------------------	------------------------

Greene Tweed Chemraz® Equivalent	Greene Tweed Chemraz 605
----------------------------------	--------------------------

Parker Parafluor® Equivalent	Parker Parafluor V8910-75
------------------------------	---------------------------

Specificaties

PPE Perlast® Equivalent

PPE Perlast G80A

Trellebrog Isolast® Equivalent

Trelleborg Isolast 9440

Overige Specs

Alternatieve benaming

FFPM – Dupont Kalrez

Chemische Benaming

Perfluoroelastomer

Extra omschrijving

O-ring 39.34x2.62 FFKM - FFPM

Merkmamen

Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum -
Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® -
HPSealing® - Perfluor® - Polymax**Technische Specs**

Compressieset

18,5 %

Soortelijk Gewicht

1,98 (+/- 0.04) g/cm³

Treksterkte

18 MPa

Ultimale Rek

145 %