



O-ring-Stocks.eu - Techniparts

Rondweg 26
8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 380,6x3,53 - FFKM - FFPM - Conform FDA - High Temp - 80 Shore A

<https://www.o-ring-stocks.eu/it/o-ring-380.6x3.53-ffkm-ffpm-alta-temp-fda-ec19352004-usp-class-vi-80-shore-a-bianco-ors92400>

Specificaties

Productnummer	92400
Merk	Eurolast
Categorie	FFKM O-Rings - 80 Shore A - F808W95 - Wit
Materiaal	FFKM - FFPM
Kleur	Wit

Basis Specificaties

Keurmerk	Conform FDA - (300°C)
Kleur	White

Afmetingen	380.6x3.53
Equivalent	PPE Perlast G80H
Materiaal	FFKM - FFPM
Omschrijving-2	O-ring FFKM - FFPM 380.6x3.53
Type Dichting	O-ring

Alternative maat

AS568 Maat	AS 009
DIN 3771 Maat	380.6x3.53
Maat in tekst	three hundred and eighty comma sixty by three comma fifty three
SMS 1586 Maat	380.6 X 3,53

Basis Specificaties

CS (Snoer dikte)	3.53 mm
Hardheid	80 Shore A
ID (Binnendiameter)	380.6 mm
Temperatuur Max	300 °C
Temperatuur Min	-15 °C

Equivalent aan

Dupont Kalrez® Equivalent	Not Known
Freudenberg Simriz® Equivalent	Not Known
Greene Tweed Chemraz® Equivalent	Not Known
Parker Parafluor® Equivalent	Not Known

Specificaties

PPE Perlast® Equivalent PPE Perlast G80H

Trelleborg Isolast® Equivalent Not Known

Overige Specs

Alternatieve benaming FFPM – Dupont Kalrez

Chemische Benaming Perfluoroelastomer

Extra omschrijving O-ring 380.6x3.53 FFKM - FFPM

Merkmamen Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax

Technische Specs

Compressieset 28 %

Soortelijk Gewicht 2,55 (+/- 0,03) g/cm³

Treksterkte 13,2 MPa

Ultimale Rek 100 %