



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 150x2.65 - FFKM - FFPM - Vapore - Acqua Calda - 75 Shore A - Nero

<https://www.o-ring-stocks.eu/it/o-ring-150x2.65-ffkm-ffpm-vapore-acqua-calda-75-shore-a-nero-kalrez-1050lf-ors108331-equivalente>

Specificaties

Productnummer	108331
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758ZSR
Materiaal	FFKM - FFPM
Kleur	Zwart
Kleur	Black

Basis Specificaties

Keurmerk	Steam. Hot Water
----------	------------------

Alternatieve benaming	FFPM – Dupont Kalrez
-----------------------	----------------------

Chemische Benaming	Perfluoroelastomer
--------------------	--------------------

Equivalent	Kalrez® 1050LF . Chemraz® 555 . Chemraz® 605 . Perflour® V8545-75 . Simriz® 487 . Isolast® J9512 . Polymax P300B8ST . Evolast N8SR
------------	--

Extra omschrijving	O-ring 150x2.65 FFKM
--------------------	----------------------

Maat in tekst	one hundred and fifty zero by two comma sixty five
---------------	--

Materiaal	FFKM - FFPM
-----------	-------------

Merknamen	Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax
-----------	---

Omschrijving-2	O-ring FFKM - FFPM 150x2.65
----------------	-----------------------------

Verpakkingseenheid	O-ring
--------------------	--------

Alternative maat

AS568 Maat	AS 437
------------	--------

DIN 3771 Maat	150x2.65
---------------	----------

ISO 3601 Maat	B1500
---------------	-------

NF T 47-501 Maat	B1500
------------------	-------

SMS 1586 Maat	150 X 2.65
---------------	------------

Basis Specificaties

CS (snoer dikte)	2.65 mm
------------------	---------

Hardheid	75 Shore A
----------	------------

ID (binnendiameter)	150 mm
---------------------	--------

Specificaties

Temperatuur Max 330 °C

Temperatuur Min -15 °C