




O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 34.52x3.53 - FKM - FPM - Viton - 70 Shore A - Verde - ORS41860

<https://www.o-ring-stocks.eu/it/o-ring-34.52x3.53-fkm-fpm-viton-70-shore-a-verde-ors41860>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 41860                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 70 Shore A - Groen |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Groen                            |
| Kleur         | Green                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                        |
|-----------------------|--------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                           |
| Chemische Benaming    | Fluorocarbon Rubber                                    |
| Extra omschrijving    | O-ring 34.52x3.53 FPM - Viton                          |
| Maat in tekst         | thirty four comma fifty two by three comma fifty three |
| Materiaal             | FKM - FPM - Viton                                      |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                |
| Omschrijving-2        | O-ring FKM - FPM - Viton 34.52x3.53                    |
| Verpakkingseenheid    | O-ring                                                 |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 220       |
| DIN 3771 Maat | 34.52x3.53   |
| SMS 1586 Maat | 34.52 X 3.53 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 34.52 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |