



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL info@o-ring-stocks.eu

TEL +31382024043

KVK 08174024

O-ring 329.57x5.33 - FFKM - FFPM - 75 Shore A - Nero - Kalrez® 6375 -

<https://www.o-ring-stocks.eu/it/o-ring-329.57x5.33-ffkm-ffpm-75-shore-a-nero-kalrez-6375-ors51290-equivalente>

Specificaties

Productnummer	51290
Merk	Eurolast
Categorie	FFKM O-Rings - 75 Shore A - F758Z94
Materiaal	FFKM - FFPM
Kleur	Zwart
Kleur	Black

Basis Specificaties

Keurmerk	General Purpose (+270°C)
----------	--------------------------

Alternatieve benaming	FFPM – Dupont Kalrez
Chemische Benaming	Perfluoroelastomer
Extra omschrijving	O-ring 329.57x5.33 FFKM
Maat in tekst	three hundred and twenty nine comma fifty seven by five comma thirty three
Materiaal	FFKM - FFPM
Merknamen	Evolast® - Chemraz® - Simriz® - Kalrez® - Spectrum - Triazinico - Isolast® - Parofluor® - Fluorez - Perlast® - HPSealing® - Perfluor® - Polymax

Omschrijving-2	O-ring FFKM - FFPM 329.57x5.33
Verpakkingseenheid	O-ring

Alternative maat

AS568 Maat	AS 455
DIN 3771 Maat	329.57x5.33
SMS 1586 Maat	329.57 X 5.33

Basis Specificaties

CS (snoer dikte)	5.33 mm
Hardheid	75 Shore A
ID (binnendiameter)	329.57 mm
Temperatuur Max	270 °C
Temperatuur Min	-20 °C