



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 244.5x8.4 - FKM - FPM - Viton - 80 Shore A - Marrone - ORS35983

<https://www.o-ring-stocks.eu/it/o-ring-244.5x8.4-fkm-fpm-viton-80-shore-a-marrone-ors35983>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 35983                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Bruin |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Bruin                            |
| Kleur         | Brown                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                                |
| Chemische Benaming    | Fluorocarbon Rubber                                         |
| Extra omschrijving    | O-ring 244.5x8.4 FPM - Viton                                |
| Maat in tekst         | two hundred and forty four comma fifty by eight comma forty |
| Materiaal             | FKM - FPM - Viton                                           |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                     |
| Omschrijving-2        | O-ring FKM - FPM - Viton 244.5x8.4                          |
| Verpakkingseenheid    | O-ring                                                      |

### Alternative maat

|                 |             |
|-----------------|-------------|
| DIN 3771 Maat   | 244.5x8.4   |
| JIS B 2401 Maat | JIS P245    |
| SMS 1586 Maat   | 244.5 X 8.4 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 8.4 mm     |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 244.5 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |