



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 109.4x3.1 - FKM - FPM - Viton - 80 Shore A - Marrone - ORS35959

<https://www.o-ring-stocks.eu/it/o-ring-109.4x3.1-fkm-fpm-viton-80-shore-a-marrone-ors35959>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 35959                            |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Bruin |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | Bruin                            |
| Kleur         | Brown                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                     |
|-----------------------|-----------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                        |
| Chemische Benaming    | Fluorocarbon Rubber                                 |
| Extra omschrijving    | O-ring 109.4x3.1 FPM - Viton                        |
| Maat in tekst         | one hundred and nine comma forty by three comma ten |
| Materiaal             | FKM - FPM - Viton                                   |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin             |
| Omschrijving-2        | O-ring FKM - FPM - Viton 109.4x3.1                  |
| Verpakkingseenheid    | O-ring                                              |

### Alternative maat

|                 |             |
|-----------------|-------------|
| DIN 3771 Maat   | 109.4x3.1   |
| JIS B 2401 Maat | JIS G110    |
| SMS 1586 Maat   | 109.4 X 3.1 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.1 mm     |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 109.4 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |