



O-ring-Stocks.eu - Techniparts

Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 621x8 - FKM - FPM - Viton - 80 Shore A - Marrone - ORS133435

<https://www.o-ring-stocks.eu/it/o-ring-621x8-fkm-fpm-viton-80-shore-a-marrone-ors133435>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 133435                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Zwart |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | BRUIN                            |
| Kleur         | Brown                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                  |
| Chemische Benaming    | Fluorocarbon Rubber                           |
| Extra omschrijving    | O-ring 621x8 FKM - FPM - Viton                |
| Maat in tekst         | six hundred and twenty one zero by eight zero |
| Materiaal             | FKM - FPM - Viton                             |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin       |
| Omschrijving-2        | O-ring FKM - FPM - Viton 621x8                |
| Verpakkingseenheid    | O-ring                                        |

### Alternative maat

|               |       |
|---------------|-------|
| DIN 3771 Maat | 621x8 |
| ISO 3601 Maat | 621x8 |
| SMS 1586 Maat | 621x8 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 8 mm       |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 621 mm     |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |