



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 439.2x5.7 - FKM - FPM - Viton - 80 Shore A - Nero - ORS144818

<https://www.o-ring-stocks.eu/it/o-ring-439.2x5.7-fkm-fpm-viton-80-shore-a-nero-ors144818>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 144818                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Zwart |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | ZWART                            |
| Kleur         | Black                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                                    |
| Chemische Benaming    | Fluorocarbon Rubber                                             |
| Extra omschrijving    | O-ring 439.2x5.7 FKM - FPM - Viton                              |
| Maat in tekst         | four hundred and thirty nine comma twenty by five comma seventy |
| Materiaal             | FKM - FPM - Viton                                               |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                         |
| Omschrijving-2        | O-ring FKM - FPM - Viton 439.2x5.7                              |
| Verpakkingseenheid    | O-ring                                                          |

### Alternative maat

|               |           |
|---------------|-----------|
| DIN 3771 Maat | 439.2x5.7 |
| ISO 3601 Maat | 439.2x5.7 |
| SMS 1586 Maat | 439.2x5.7 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 5.7 mm     |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 439.2 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |