



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 23.58x3.53 - FKM - FPM - Viton - 80 Shore A - Rosso - ORS184253

<https://www.o-ring-stocks.eu/it/o-ring-23.58x3.53-fkm-fpm-viton-80-shore-a-rosso-ors184253>

### Specificaties

|               |                                  |
|---------------|----------------------------------|
| Productnummer | 184253                           |
| Merk          | Eurolast                         |
| Categorie     | FKM O-Rings - 80 Shore A - Groen |
| Materiaal     | FKM - FPM - Viton                |
| Kleur         | GROEN                            |
| Kleur         | Green                            |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                           |
|-----------------------|-----------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                              |
| Chemische Benaming    | Fluorocarbon Rubber                                       |
| Extra omschrijving    | O-ring 23.58x3.53                                         |
| Maat in tekst         | twenty three comma fifty eight by three comma fifty three |
| Materiaal             | FKM - FPM - Viton                                         |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin                   |
| Omschrijving-2        | O-ring FKM - FPM - Viton 23.58x3.53                       |
| Verpakkingseenheid    | O-ring                                                    |

### Alternative maat

|               |              |
|---------------|--------------|
| DIN 3771 Maat | 23.58 x 3.53 |
| SMS 1586 Maat | 23.58x3.53   |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 80 Shore A |
| ID (binnendiameter) | 23.58 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |