



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 47.29x2.62 - FKM - FPM - Viton - AED - Pressione - Bassa Temp - 90

<https://www.o-ring-stocks.eu/it/o-ring-47.29x2.62-fkm-fpm-viton-aed-pressione-bassa-temp-90-shore-a-nero-ors67349>

### Specificaties

|               |                                    |
|---------------|------------------------------------|
| Productnummer | 67349                              |
| Merk          | Eurolast                           |
| Categorie     | FKM O-Rings - 90 Shore A - PLT/AED |
| Materiaal     | FKM - FPM - Viton                  |
| Kleur         | Zwart                              |
| Kleur         | Black                              |

### Basis Specificaties

|          |           |
|----------|-----------|
| Keurmerk | PLT / AED |
|----------|-----------|

|                       |                                                      |
|-----------------------|------------------------------------------------------|
| Alternatieve benaming | Viton® - FKM                                         |
| Chemische Benaming    | Fluorocarbon Rubber                                  |
| Extra omschrijving    | O-ring 47.29x2.62 FPM - Viton                        |
| Maat in tekst         | forty seven comma twenty nine by two comma sixty two |
| Materiaal             | FKM - FPM - Viton                                    |
| Merknamen             | Viton® - Du Pont - 3M - Solvay - Daikin              |
| Omschrijving-2        | O-ring FKM - FPM - Viton 47.29x2.62                  |
| Verpakkingseenheid    | O-ring                                               |

### Alternative maat

|               |              |
|---------------|--------------|
| AS568 Maat    | AS 034       |
| DIN 3771 Maat | 47.29x2.62   |
| SMS 1586 Maat | 47.29 X 2.62 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 2.62 mm    |
| Hardheid            | 90 Shore A |
| ID (binnendiameter) | 47.29 mm   |
| Temperatuur Max     | 205 °C     |
| Temperatuur Min     | -20 °C     |