



O-ring-Stocks.eu - Techniparts

Rondweg 26

8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)

TEL +31382024043

KVK 08174024

## O-ring 120.24x3.53 - HNBR - AED - 90 Shore A - Nero - ORS176110

<https://www.o-ring-stocks.eu/it/o-ring-120.24x3.53-hnbr-aed-90-shore-a-nero-ors176110>

### Specificaties

|               |                                   |
|---------------|-----------------------------------|
| Productnummer | 176110                            |
| Merk          | Eurolast                          |
| Categorie     | HNBR O-Rings - 70 Shore A - Zwart |
| Materiaal     | HNBR - Buna                       |
| Kleur         | ZWART                             |
| Kleur         | Black                             |

### Basis Specificaties

|          |     |
|----------|-----|
| Keurmerk | AED |
|----------|-----|

|                       |                                                                     |
|-----------------------|---------------------------------------------------------------------|
| Alternatieve benaming | Hydrogenated Nitrile Butadiene Rubber                               |
| Chemische Benaming    | Hydrogenated nitrile rubber                                         |
| Extra omschrijving    | O-ring 120.24x3.53                                                  |
| Maat in tekst         | one hundred and twenty comma twenty four by three comma fifty three |
| Materiaal             | HNBR                                                                |
| Merknamen             | Lanxess - Zeon - and LG Chem                                        |
| Omschrijving-2        | O-ring HNBR - 120.24x3.53                                           |
| Verpakkingseenheid    | O-ring                                                              |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 112        |
| DIN 3771 Maat | 120.24 x 3.53 |
| SMS 1586 Maat | 120.24x3.53   |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 3.53 mm    |
| Hardheid            | 90 Shore A |
| ID (binnendiameter) | 120.24 mm  |
| Temperatuur Max     | 150 °C     |
| Temperatuur Min     | -25 °C     |