



O-ring-Stocks.eu - Techniparts  
Rondweg 26  
8091XB, Wezep

E-MAIL [info@o-ring-stocks.eu](mailto:info@o-ring-stocks.eu)  
TEL +31382024043  
KVK 08174024

## O-ring 183.52x6.99 - HNBR - 70 Shore A - Verde - ORS50027

<https://www.o-ring-stocks.eu/it/o-ring-183.52x6.99-hnbr-70-shore-a-verde-ors50027>

### Specificaties

|               |                                   |
|---------------|-----------------------------------|
| Productnummer | 50027                             |
| Merk          | Eurolast                          |
| Categorie     | HNBR O-Rings - 70 Shore A - Groen |
| Materiaal     | HNBR - Buna                       |
| Kleur         | Groen                             |
| Kleur         | Green                             |

### Basis Specificaties

|          |      |
|----------|------|
| Keurmerk | None |
|----------|------|

|                       |                                                                       |
|-----------------------|-----------------------------------------------------------------------|
| Alternatieve benaming | Hydrogenated Nitrile Butadiene Rubber                                 |
| Chemische Benaming    | Hydrogenated nitrile rubber                                           |
| Extra omschrijving    | O-ring 183.52x6.99 HNBR                                               |
| Maat in tekst         | one hundred and eighty three comma fifty two by six comma ninety nine |
| Materiaal             | HNBR                                                                  |
| Merknamen             | LG Chem - Lanxess and Zeon                                            |
| Omschrijving-2        | O-ring HNBR - 183.52x6.99                                             |
| Verpakkingseenheid    | O-ring                                                                |

### Alternative maat

|               |               |
|---------------|---------------|
| AS568 Maat    | AS 442        |
| DIN 3771 Maat | 183.52x6.99   |
| SMS 1586 Maat | 183.52 X 6.99 |

### Basis Specificaties

|                     |            |
|---------------------|------------|
| CS (snoer dikte)    | 6.99 mm    |
| Hardheid            | 70 Shore A |
| ID (binnendiameter) | 183.52 mm  |
| Temperatuur Max     | 150 °C     |
| Temperatuur Min     | -25 °C     |